


TETRA

Low-Cost Line Scan Cameras



KEY FEATURES

- Low-cost
- Single line/HDR/TDI
- Multiple regions of interest for calibration and data reduction
- Programmable coefficient sets
- Programmable I/Os
- 2.5 GigE Vision
- Power over Ethernet

TYPICAL APPLICATIONS

- Electronics
- Printed circuit boards
- Packaging
- Film, glass and web
- Wood inspection
- Print inspection
- General machine vision



Tetra 2.5 GigE monochrome cameras

The Tetra camera is remarkably cost effective, making line scan technology more accessible than ever. Using Teledyne DALSA's latest line scan sensor technology, it delivers superior image quality, high dynamic range, and low power consumption using a 2.5 GigE Vision® interface for many cost sensitive applications.

SPECIFICATIONS

Part Number	TL-GM-02k15B	TL-GM-04k07B	TL-GM-08K07S
Resolution, pixel	2,048 x 2	4,096 x 2	8,192x1
Line Rate, kHz	150	75	75
Pixel Size, µm	14 x 14	7 x7	3.5x3.5
Data Format, bit	8/10		
Dynamic Range, dB	70		
Full Well, ke-	30		
Read Noise, e-	9		
Power Dissipation, W	<6		
Operating Temp, °C	0 to +55		
Dimension, mm	62 (W) x 62 (H) x 50 (D)		
Weight, g	297		
Lens Mount	M42 x 1		
Data Interface	2.5GigE Vision, RJ45		
Power and GPIO	+12 to +24VDC or PoE, Hirose-12		

SPECIFICATIONS



FOR MORE INFORMATION CONTACT:

THE AMERICAS	Boston, USA +1-978-670-2000 TDI_sales.americas@teledyne.com
EUROPE	Munich, Germany +49-89-89-54-57-3-80 TDI_sales.europe@teledyne.com
JAPAN & ASIA PACIFIC	Tokyo, Japan +81-3-5960-6353 TDI_sales.asia@teledyne.com
SHANGHAI OFFICE	Shanghai, China +86-21-60131571 ext. 801 saleschina@teledyne.com

This document does not contain information whose export/transfer/disclosure is restricted by the Canadian Export Control regulation. Teledyne DALSA has its corporate offices in Waterloo, Canada. Teledyne DALSA reserves the right to make changes at any time without notice. 2025 © Teledyne DALSA.

Revision Number: 03-070-25023
Revision Date: 2025 04 24