


Vision Components

[OPT \(/\)](#) > [Product \(/product/\)](#) > [Vision Components Series \(/product/index6.html\)](#) > [Frame Grabbers \(/content/details96_4049.html\)](#) > [GigE Card](#)

GigE Card

Features:

- ◆ Intel I350 server-grade Gigabit Ethernet controller
- ◆ Simultaneous connection of 2/4 independent PoE GigE interfaces designed with 4× PCIe gen2.0
- ◆ Complying with IEEE802.3 af and IEEE1588 standards
- ◆ PoE technology applied to greatly reduce cost in
- ◆ installation and maintenance



 [Request a quote \(/](#)

[service/consultant.html\)](#)

SpecificationsDownloads



Functions:

- ◆ 2 or 4 independent GigE ports available
- ◆ 15.4W 1000Mb/s provided by each port
- ◆ Max. 100m transmission via CAT-5/CAT-6 cable
- ◆ Link aggregation and 9.5KB jumbo frame
- ◆ 8 receive side scaling queues and 2048 receive and transmit buffers
- ◆ Power supplied by PCIe bus; When PoE <35W, external power supply is not required.

(/)

Specifications:

Model	SCI-GEP-4
Connection Interface	PCI Expressx4
Network Interface	4× GigE ports by Intel I350-AM4 controller,supporting 9.5KB jumbo frame and (8) VMDq
PoE Performance	Complying with IEEE 802.3af, each port delivers up to 15.4W of power
Cable Transmission Distance	Max. 100m via CAT-5/CAT-6 cable
Required Power	①Max. 3.3V@2.4A from PCIe slot (mailto:①PCIe插槽需求3.3V@2.4A) ②Max. 12V@5.6A (mailto:①PCIe插槽需求3.3V@2.4A) or 24V@3A from external power supply
Operating Temperature	-10°C~55°C(14°F~131°F)
Operating Humidity	10% - 85%, non-condensing
Storage Temperature and Humidity	-40°C~80°C(-40°F~176°F); 0~80%

[Products \(/product/\)](#)

[Support \(/service/\)](#)

[Resources \(/train/\)](#)

[Company \(/about/\)](#)

Support hotline

+86-400-0769-068 (tel:+86-400-0769-068)

Useful Link

